



Countertop Texture Blend

Product Information

Description:

This engineered product is an essential element for the Granicrete Countertop Surfacing System. Its significant characteristics include:

1. Excellent adhesion to existing countertop surfaces for “resurfacing” purposes.
2. Excellent adhesion for MDF and MDX for new installation purposes.
3. Wipe-away technology permitting the Certified Installer to literally “wipe away” topical colors within 30-45 of application in order to easily start desired coloring over again.
4. This proprietary formulation provides for optimal color enhancement of topical coloring to yield the exceptionally authentic looks for granite, marble, and other stone effects desired in high-end counter tops.

Uses:

In addition to Granicrete countertops, it is used for Granicrete’s Shower FX system, and as a primer or topcoat for the Granicrete Alternative Flooring system.

Coverage:

Coverage for 40 pound pail is 60 square feet (at 1/16 inch) per use under the Granicrete Countertop Surfacing System.

Surface Preparation:

For best results, the surface to be covered must be dry and free of dust, wax, grease, or oil.

Measuring:

Using the prescribed ration of Granicrete Texture Blend to water as instructed in the System manual produces best results.

Mixing Tools:

Mixing container- Should have smooth flat bottom and be clean and dust free.

Mixing Paddle - Must use drill and paddle mixer assuring until texture is thoroughly mixed having no clumps. Period mixing is recommended to maintain texture consistency throughout installation.

Mixing and Application:

Certified Installers must reference Granicrete’s Countertop Training Manual per the individual stages required.

Drying Time:

Drying time is enhanced with warmer ambient temperature and moving air. Do not apply direct heat to surface.

Clean Up:

Clean up Granicrete Countertop Texture Blend should be done while it is in its liquid state. After it has been cured, it can be removed by mechanical grinding. Therefore, it is advisable to clean your tools immediately after use.

Technical Data:

COMPRESSIVE STRENGTH: ASTM C109	
@ 24 hours	950 psi
@ 7 days	3,120 psi
@ 28 days	4,150 psi
FLEXURAL STRENGTH: ASTM C78	
@ 24 hours	350 psi
@ 7 days	1,090 psi
@ 28 days	1,410 psi
<i>Independent laboratory tests were conducted and certified by Western Technologies, Inc. “The <u>Quality</u> People Since 1955”</i>	

This product is for use by Granicrete Independent Certified applicators only.
Wear Personal Protective Equipment.
Read MSDS before using this product.

Manufacturer/Distributor Warranty: As neither the manufacturer nor the distributor has control over the actual installation of this product, the manufacturer and distributor disclaim any and all warranties expressed or implied regarding color shade, appearance, and product performance at and after opening product containers. Manufacturer and distributor recommendations and suggestions are made without guarantee. Conditions of installer’s and consumer’s use of this product are beyond the control of manufacturer and distributor. Manufacturer and distributor disclaim any liability incurred in connection with the use of this product or information contained herein.