



## GraniMax Wall Décor

### Product Information

---

#### *Description & Use*

- This high-tech one-step interior veneer plaster yields exceptional strength while offering broad artistic opportunities.
- Simply add water and apply either in single coat scratch or a finish coat application.
- Providing speed and ease, this product surpasses conventional plasters in performance, artistic options, and life.

#### *Significant Characteristics*

- GraniMax Wall Décor emits no pollutants and is composed of recycled products that are environmentally responsible and sustainable.
- Being 98% silica free, it has high tolerances for mold and mildew growth.
- Application and finishing can be done through spraying and troweling. Finished artistic applications include knock down, slick trowel, sponge, brush, rubber float, skip trowel and other custom finishes.
- Coloring may be done integrally

#### *Coverage*

- As a skim coat ó 1 pound per 2 square feet
- At 1/8ö ó 1 pound per square foot for smooth coat finish
- At ¼ö ó 2 pounds per square foot for heavy texture applications

#### *Surface Preparation*

- Over existing drywallí prime with Granicrete's Superstrength Polymer Resin.
- Over new drywallí standard drywall tape and joint compound
- Over cement boardí joints should be taped using alkali resistant fiberglass mesh tape.
- Over concrete surfacesí free of oil, grease, latex compounds, paint, sealers and other bond-breaking compounds.

### ***Measuring & Mixing***

- Potable water should be less than 75°F and at least 50°F
- 3 quarts water per 50 lb bag and should be fairly precise
- Put water in mixing bucket and then add ½ bag if GraniMax Wall Décor.
- Mix for 304 minutes. Once mixed (using a mixing paddle or direct drive mixer at 500-600rpm) then add the remaining dry mix and blend for 1 minute.
- Allow to sit for one minute then resume mixing for two minutes until smooth and without lumps.
- NOTE: During the mixing period it is common to have the material appear to be too dry. Continue to mix even if it appears to be stiff. After four minutes, small amounts of water may be added but not more than 7.5 ounces for the entire bag.
- Do not water after the final mixing.
- Ideal application of material takes place between 50°F and 95°F with a relative humidity of 40% or greater.

### ***Drying Time***

- Excessive heat or low humidity may cause cracking. Misting or wrapping is advised in such conditions. The warmer your temperature the greater should be your humidity.
- In excessive heat, reduce air movement. In colder environments, air movement is acceptable.

### ***Painting***

- Material must be dry before topical coloration. If topical coloring is desired, priming is advised.

### ***Sealing***

- Sealing can be done with water-based acrylic, solvent based acrylic, silicone or siloxane sealers.

### ***Clean Up***

- Clean promptly with water.

### ***Technical Data***

GraniMax Wall Décor has met or exceeded the following Compliance Standards:

- ASTM C109 Compressive strength standard: Over 4,000 psi in 7 days
- ASTM C587 Gypsum Veneer Plaster
- ASTM C1629 Impact/Abrasion Resistance
- ASTM E84 Flame Spread Resistance: Zero Flame Spread, Zero Smoke

- ASTM E136 Building Material Combustibility
- ASTM G21 Fungal Contamination Resistance
- Exceeds USEPA and CA indoor air quality VOC requirements.

***Safety & Protection:***

- Read Material Safety Data Sheets before Use

***Miscellaneous:***

- Shelf life with proper indoor storage is one year from manufacture date.
- In humid environments, once container is opened, unused product should be discarded.
- For Interior Use Only

This product is for use by Granicrete Independent applicators only. Wear Personal Protective Equipment.  
Read MSDS before using this product.  
DOT/Flash Point . Non-flammable Classification not regulated.

**Manufacturer/Distributor Warranty:** As neither the manufacturer nor the distributor has control over the actual installation of this product, the manufacturer and distributor disclaim any and all warranties expressed or implied regarding color shade, appearance, and product performance at and after opening product containers. Manufacturer and distributor recommendations and suggestions are made without guarantee. Conditions of installer's and consumer's use of this product are beyond the control of manufacturer and distributor. Manufacturer and distributor disclaim any liability incurred in connection with the use of this product or information contained herein.